



WELD STUD, DISCHARGER CAPACITOR

STANDARD	GB/T902,3 , ISO13918
GRADE	4,8
SIZES	M3 - M16
SURFACE TREATMENT	COPPER



WELD STUD, DISCHARGER CAPACITOR

STANDARD	GB/T902,3 , ISO13918
GRADE	4,8
SIZES	5/32, UNTIL 2" (UNDER REQUEST)
SURFACE TREATMENT	COPPER



Thread Size (Thd)	Length (L)	Flange (FL)	Thickness (Thk)
M 3	10	4,5	0,7 - 1,4
M 3	12	4,5	
M 3	16	4,5	
M 3	20	4,5	
M 4	10	5,5	
M 4	12	5,5	
M 4	16	5,5	
M 5	10	6,5	
M 5	12	6,5	
M 5	15	6,5	
M 5	16	6,5	
M 6	10	7,5	
M 6	12	7,5	
M 6	15	7,5	
M 6	20	7,5	
M 8	10	9,5	0,8 - 1,4
M 8	12	9,5	
M 8	20	9,5	
M 8	25	9,5	
M 10	10	11,5	
M 10	12	11,5	
M 10	15	11,5	
M 10	20	11,5	
M 12	10	13,5	
M 12	20	13,5	
M 16	10	17,5	
M 16	12	17,5	
M 16	16	17,5	

Thread Size (Thd)	Length (L)	Flange (FL)	Thickness (Thk)
5/32"	1/2"	0,218 in	0,030 in
5/32"	1/4"	0,218 in	
5/32"	1"	0,218 in	
5/32"	1 1/2"	0,218 in	
5/16"	1/4"	0,250 in	
5/16"	3/4"	0,250 in	
5/16"	1/2"	0,250 in	
5/16"	1"	0,250 in	
5/16"	1 1/4"	0,250 in	
3/16"	3/4"	0,250 in	
3/16"	1/4"	0,250 in	
3/16"	1/2"	0,250 in	
3/16"	3/8"	0,250 in	
3/16"	1"	0,250 in	
3/16"	1 1/2"	0,250 in	
1/4"	3/4"	0,250 in	
1/4"	1/2"	0,250 in	
1/4"	1/8"	0,250 in	
1/4"	1"	0,250 in	
1/4"	1 1/2"	0,250 in	
1/4"	1 1/4"	0,250 in	
1/8"	3/4"	0,218 in	
1/8"	1/2"	0,218 in	
1/8"	1/8"	0,218 in	
1/8"	1"	0,218 in	
1/8"	1 1/2"	0,218 in	