



| INSULATED SPADE TERMINALS                               |     |                      |           |           |           |           |             |        |
|---|-----|----------------------|-----------|-----------|-----------|-----------|-------------|--------|
| 0.5 ~ 1.5mm <sup>2</sup> (22-16) I <sub>max</sub> = 19A |     |                      |           |           |           |           |             |        |
| REFERENCE   | #   | SCREW DIA<br>D2 (MM) | B<br>(MM) | L<br>(MM) | F<br>(MM) | H<br>(MM) | D φ<br>(MM) | COLOR  |
| HT-VI.25-3  | #4  | 3.2                  | 5.7       | 21.2      | 6.5       | 10.0      | 4.3         | RED    |
| HT-VI.25-4  | #8  | 4.3                  | 6.4       | 21.2      | 6.5       |           |             |        |
| HT-SI.25-5  | #10 | 5.3                  | 8.1       | 21.2      | 6.5       |           |             |        |
| 1.5 ~ 2.5mm <sup>2</sup> (16-14) I <sub>max</sub> = 27A |     |                      |           |           |           |           |             |        |
| REFERENCE   | #   | SCREW DIA<br>D2 (MM) | B<br>(MM) | L<br>(MM) | F<br>(MM) | H<br>(MM) | D φ<br>(MM) | COLOR  |
| HT-SV2-3  | #4  | 3.2                  | 5.7       | 21.2      | 6.5       | 10.0      | 4.9         | BLUE   |
| HT-SVS2-4   | #8  | 4.3                  | 6.0       | 21.2      | 6.5       |           |             |        |
| HT-SVS-2-5  | #10 | 5.3                  | 8.1       | 21.2      | 6.5       |           |             |        |
| 4 ~ 6mm <sup>2</sup> (12-10) I <sub>max</sub> = 48A     |     |                      |           |           |           |           |             |        |
| REFERENCE   | #   | SCREW DIA<br>D2 (MM) | B<br>(MM) | L<br>(MM) | F<br>(MM) | H<br>(MM) | D φ<br>(MM) | COLOR  |
| HT-SVS5.5-4   | #8  | 4.3                  | 8.3       | 25.2      | 7.5       | 12.5      | 6.7         | YELLOW |